



Printgen EG-1026

1) Summary

Matsumin Printgen EG-1026 is an anti-clogging agent to prevent clogging in printing process of pigment without reducing fastness of finished fabric and tremendously improve color levelness of the print, and also penetration and screen sharpness.

Besides, Printgen EG-1026 is in a paste form; therefore, it does not reduce the viscosity of the printing paste.

2) Nature

Printgen EG-1026	
Appearance	Colorless semi-transparent paste
Viscosity	500 ± 100 mPa · s
pH	7.9 ± 0.5

3) Usage

Add 2-5% in pigment or dyestuff colored paste.

If added more than 5%, it may deteriorate the fastnesses and the color value.

4) N.B.

• A proper heat curing after the print, 135-140°C x 2-3 mins., must be arranged without fail.

Recommended Parameters

Fabric Types



Screen Mesh



Squeegee



Flash & Cure



140°C x 2-3min.

Pigment



AUXILIARIES



Storage



5°C~30°C

Clean Up



Warm water
and mild detergent



MATSUI SHIKISO CHEMICAL CO.,LTD.

64 Kamikazan Sakuradani-cho,
Yamashina-ku,
Kyoto 607-8466 Japan

T : 81-75-594-5612

F : 81-75-594-0829

E : export-sales@msc-color.co.jp

W : www.msc-color.co.jp

The above information is based on our knowledges and experiences currently available. Please, test and evaluate before the actual use.